

# Silent<sup>+</sup> Mini Aqua<sup>®</sup>

## CONDENSATE REMOVAL PUMP

The Silent<sup>+</sup> Mini Aqua keeps its sleek and slender form offering unparalleled installation flexibility. It fits neatly into trunking and inside mini split units. Packed with our proven 5th Gen Technology, it's unbeatable silence – a barely audible 16dB(A)\*, combined with intelligent, adaptive flow rates – further extends pump life, maximises reliability and improves energy efficiency. Quietly brilliant.



35L/h max. flow

10m max. rec. head

As low as 16dB(A)\*

#### **Key Features**

- Slim profile
- Proven 5th Gen Technology: Capactance Sensing & Rotary Diaphragm = Silence & Power
- Low maintenance
- Plug and play\*\*
- 3 year warranty

### **Suitability**

Silent\* MINI AQUA


- Up to 40kW / 136,000Btu/h
- Ducted units; floor standing & chassis units; high wall mini split systems

• Perfect for... smaller commercial and domestic applications, where silence is needed





213mm	




Silent<sup>+</sup> Mini Aqua (5th Gen, Europe) FP3420

#### IN THE BOX

Silent<sup>+</sup> Mini Aqua 5th Gen pump • Reservoir (inc. filter and lid) • 1.5m plug and play cable\*\* • 1.5m clear PVC tube • 150mm clear vent hose • 220mm blue inlet hose • Drain connector kit: straight connector and rubber elbow • Quick start guide

Download full manual at aspenpumps.com



SUGGESTED XTRA ACCESSORIES		
Description	Part No.	
Hose Clamp 10.1 dia. (x10)	-98 взз40	
S <sup>+</sup> Mini Pump spare filters (x10)	<b>FP3330</b>	
Barbed anti-siphon device	FP3336/1	
Reservoir copper mesh filter (x10)	FP3460	



Visit aspenpumps.com for more installation accessories.

SPECIFICATIONS		
Max. flow	35L/h @ 0m head	
Max. rec. head	10m	
Max. suction lift	1.5m	
Min. dB(A) @ 1m	16dB(A)*	
Power supply	100-250VAC, 0.18A, 2.4W, 50/60 Hz	
Rated	Continuous	
Class	II 🔲	
Max. unit output	40kW (136,000Btu/h)	
Max. ambient temp	40°C (104°F)	
IP Protection	IP24	
Inlet o/d	Ø16mm (5/8")	
Outlet o/d	Ø6mm (1/4")	
Safety switch	5.0 A Normally closed	
Self priming	1	

\* Assuming solid wall construction with a 2kW unit

\*\* Not backwards compatible

Information correct at time of going to press. Not all products are available in all regions